



BI285-680RD

1U Barebone Computer with MX680RD Mini ITX,
Expansion Card cutout for PCIe x16 card

Features

- Motherboard: MX680RD Mini ITX Motherboard Inside
- LGA 1700 socket supports 13th Gen Intel® Raptor Lake Intel® Core™ i9/i7/i5/i3 Processor
- Intel® Integrated UHD Graphic with Xe Architecture (CPU Dependent)
- Intel® R680E PCH, x4 Gen4 DMI
- 2 x SODIMM sockets support Dual Channel DDR5 4800MHz up to 64GB with ECC support
- 4 x DP++
- 6 x USB 3.2 Gen 2x1 Type-A (Rear I/O)
- 2 x USB 2.0 or 3.2 Gen 2x1 (Front I/O)
- 1 x USB 3.2 Gen 2x2 Type-C
- 2 x Intel® I225-V 2.5GbE LAN
- Phoenix Type Power Connector
- Slim 1U Chassis: 10" (W) x 8.86" (D) x 1.83" (H)
- One expansion card cutout for PCIe cards
- Please note: the 4-LAN PCIe card shown in the photo is not included



Specifications

| System | |
|-----------------------|---|
| Motherboard | MX680RD Mini-ITX |
| CPU | LGA 1700 socket supports 12th Gen Intel® Alder Lake/13th Gen Intel® Raptor Lake Intel® Core™ i9/i7/i5/i3, Pentium, Celeron Processors |
| System Chipset | Intel® R680E PCH |
| DMI | x8 Gen4 DMI |
| System Memory | 2 x SODIMM sockets support Dual Channel DDR5 4800MHz up to 64GB with ECC support |
| BIOS | AMI uEFI BIOS, 256Mb SPI Flash ROM |
| Chipset | Intel® Integrated UHD Graphic with Xe Architecture (CPU Dependent) |
| Ethernet | LAN 1: Intel® I225-LM 2.5 Gigabit Ethernet Controller LAN 2: Intel® I225-LM 2.5 Gigabit Ethernet Controller |
| Audio | Realtek HD Audio |
| Expansion | 1 x M.2 M-Key 2242/2280 NVMe (PCIe x4 + SATA III) 1 x M.2 E-Key 2230 with CNVi Support (PCIe x1 + USB 2.0) |
| TPM | TPM 2.0 |
| OS Support | Windows 10, Windows 11, Linux |
| I/O - Front | |
| USB | 2 x USB 2.0 or 3.2 Gen 2x1 |
| Power | 1 x Power Button with LED |
| Other | 1 x Reset Switch |
| I/O - Rear | |
| Display | 4 x DP++ |
| USB | 6 x USB 3.2 Gen 2x1 Type-A 1 x USB 3.2 Gen 2x2 Type-C |
| LAN | 2 x RJ45 |
| Audio | Line-out, Mic-in |
| Power Connector | 1 x 4-pin Phoenix Type Power Connector |
| Expansion Card Cutout | One expansion card cutout slot for PCIe cards Please note: the 4-LAN PCIe card shown in the photo is not included |

| Power Requirement | |
|----------------------------|--|
| Requirement | 12V-24V Wide Range |
| Adapter | Input: 100~240 Vac/50~60Hz Output: 200W Adapter (24V @ 8.33A) |
| Mechanical and Environment | |
| Operating Temp | 0°C ~ 35°C (32°F ~ 95°F) |
| Storage Temp | -20°C ~ 80°C (-4°F ~ 176°F) |
| Operating Humidity | 10% ~ 86% Relative Humidity, Non-condensing |
| Certification | CE, FCC Class A, RoHS Compliant |
| Dimensions | 10" W x 8.86" D x 1.83" H (254mm W x 225.060mm D x 46.53mm H) |
| Weight | 4.25 lbs |



| Ordering Info | |
|---------------|---|
| BI285-680RD | Barebone Computer with MX680RD Mini ITX inside. 1 x expansion card cutout for PCIe card. PCIe card is NOT included. Power Adapter included. |

* All product specifications and images are subject to change without notice. Last update: 06/27/2024



BCM Advanced Research
11 Chrysler, Irvine, CA 92618 USA
An Industry Leader in Industrial Motherboards &
Embedded Computing

www.bcmcom.com
BCMSales@bcmcom.com
(949) 470-1888