




MX-PTL

Mini ITX Motherboard built with the Intel® Core™ Ultra Processor Series 3 onboard

Key Features


- Intel® Core™ Ultra Series 3 Processor onboard, formerly the Panther Lake H Platform
- 2 x DDR5 So-DIMM sockets support up to 128GB 7200 MHz
- 1 x Gen5 PCIe x8 (x16 Physical Slot)
- 3 x M.2: E-Key, M-Key, B-Key
- Integrated Intel® Arc™ B390 GPU (X7/X9 series), Intel® Graphics (5/7/9 series)
- Supports 4 Independent Displays: 2 x DP, LVDS/eDP optional, 2 x Type C Thunderbolt 4
- 2 x USB Type C Thunderbolt 4
- Dual LAN: 2 x Intel® Ethernet Controller I226-LM
- 4 x COM Ports
- 12V~24V DC-In



Product Specifications

System		Ethernet	
Processor	Intel® Core™ Ultra Series 3 Processors, formerly Panther Lake H Platform, up to 65W TDP: Intel Core Ultra X9 Processor 388H, 18M Cache, up to 5.10 GHz Intel Core Ultra 9 Processor 386H, 18M Cache, up to 4.90 GHz Intel Core Ultra X7 Processor 368H, 18M Cache, up to 5.00 GHz Intel Core Ultra 7 Processor 366H, 18M Cache, up to 4.80 GHz Intel Core Ultra 7 Processor 365, 12M Cache, up to 4.80 GHz Intel Core Ultra X7 Processor 358H, 18M Cache, up to 4.80 GHz Intel Core Ultra 7 Processor 356H, 18M Cache, up to 4.70 GHz Intel Core Ultra 7 Processor 355, 12M Cache, up to 4.70 GHz Intel Core Ultra 5 Processor 338H, 18M Cache, up to 4.70 GHz Intel Core Ultra 5 Processor 336H, 18M Cache, up to 4.60 GHz Intel Core Ultra 5 Processor 335, 12M Cache, up to 4.60 GHz Intel Core Ultra 5 Processor 325, 12M Cache, up to 4.50 GHz Note: Select SKUs require MOQ/BTO.	Controller	2 x Intel® Ethernet Controller I226-LM
Memory	2 x DDR5 So-DIMM sockets support up to 128GB 7200 MHz Max	Interface	2 x 10/100/1000/2.5G Base-Tx GbE Compatible
BIOS	256Mb SPI BIOS	Connector	2 x RJ45 LAN
Audio Codec	Realtek HD Audio Codec	External I/O Ports	
TPM	TPM 2.0	Display	2 x DisplayPort++ (Vertical Connectors)
Supported OS	Win 11 64-bit Linux Ubuntu	USB	2 x USB 3.2 Gen 2 Type A Connectors 2 x USB 2.0 Type A Connectors 2 x USB Type C Thunderbolt 4 Connectors
Display		LAN	2 x RJ45
Chipset	Integrated Intel® Xe3 Graphic	Audio	Line-out
Display Output	2 x DisplayPort 2.1 (HBR3) 18/24-bits Dual Channel LVDS, optional eDP	DC-in	1 x Barrel Type DC-in Connector
Multi-Display	Supports 4 Independent Displays	Internal I/O Ports	
Expansion Interfaces		Display	1 x 2 LANE MIPI-CSI Connectors 1 x LVDS Header, 1 x eDP Header (Optional)
PCI Express	1 x Gen5 PCIe x8 (x16 Physical Slot) (H484 CT & H404 ET Only)	USB	1 x USB 3.2 Header (2 x USB 3.2 Gen 1 Ports) 1 x USB 2.0 Header (2 x USB 2.0 Ports)
M.2	1 x 2230 M.2 E-Key with CNVi Support (PCIe x1 Channel & USB Signal) 1 x 2280 & 2242 M.2 M-Key NVMe (with Gen 5 PCIe x4) 1 x 3042 M.2 B-Key with Nano SIM Socket (with PCIe x2, & USB 3.2 Signal)	COM Port	2 x RS-232/422/485 Header (COM1/ COM2) (RS485, RS422 up to 10Mbps) 2 x RS-232 Header (COM3, COM4) up to 1.5Mbps
		GPIO	1 x 8 bits GPIO Header (4 In/4 Out)
		DC-in	1 x 4-Pin DC-In Connector
		MIO	1 x I2C Header, CPU Fan Header, System Fan Header, Front Audio Header, Front Panel Header, Amplifier Locking Type Header, CR2032 Wired Battery, Onboard Buzzer

Product Photo



Mechanical, Power, and Environment	
Power Requirement	12V~24V DC-In
Operating Temperature	0°C to 60°C (32°F ~ 140°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Operating Humidity	5% ~ 90% Relative Humidity, Non-condensing
Cooling Design	Active CPU Cooler (Optional Passive Cooler for Under 15W TDP)
Form Factor	Mini ITX
Dimensions	6.7" x 6.7" (170mm x 170mm)
Weight	4.85lbs (2.2 kg)
Regulatory Compliance	FCC Class B/CE RoHS and REACH Compliant
Weight	0.88 lbs (0.4 KG)

Ordering Information

Part No.	Description
MX-PTL	Mini-ITX with Intel® Core™ Ultra Processor Series 3. Please contact BCMSales@bcmcom.com
Accessory Included	1 x SATA Power Cable for Two Devices, 1 x Full Height I/O Shield, 1 x Low-profile I/O Shield



BCM ADVANCED RESEARCH
Intel Prestige Partner - Builder
11 Chrysler, Irvine, CA 92618 | (949)470-1888
BCMSales@bcmcom.com | www.bcmcom.com

